



Velocity Credential Enrollment Solutions

Fast, Accurate, and Secure Enrollment



Streamline contactless credential enrollment into Identiv's Velocity security management system.

Through a standard USB connection to the Velocity client, Identiv's Velocity Credential Enrollment Solutions send credential data directly into the Velocity Enrollment Manager through a USB Virtual COM interface.

There is no dependency on cursor location when enrolling a credential. The card data is immediately processed into the MATCH code to ensure there are no data entry errors or misinformation.

Fast and Accurate Enrollment

- Enroll credentials with a single touch
- Read all credential types supported by TS readers

Integrates to Velocity

- USB virtual COM interface to Velocity Enrollment Manager
- Scans card data into a MATCH conversion

Flexibility

- Enrollment Base Station supports most Wiegand readers
- No need to know the card number

Options

Choose between two Velocity Credential Enrollment Solutions platforms.

1. A complete enrollment station (SMES-TS-USB) that includes a TS Wall Mount reader, enrollment stand, cables and plug-in power supply. This multi-technology platform enrolls 13.56 MHz high-frequency (HF) and 125 kHz proximity (LF) credentials.
2. A base enrollment station (SMES-U-USB) with enrollment stand, cables and plug-in power supply that supports adding a reader of your choice. Examples include custom TS firmware, HID iCLASS, or most any Wiegand reader compatible with the credentials being used. Any wall mount or keypad configuration will fit the mounting plates. (Note: MobilisID is not compatible.)

Consult the TS Reader Ordering Guide to identify the hardware configuration that meets your needs.

Organizations that have custom TS Reader configurations can contact their Regional Sales Manager for a custom version.

Velocity Credential Enrollment Solutions

Part Number	SMES-TS-USB	SMES-U-USB
Description	TS USB Enrollment Station	Universal USB Virtual COM Enrollment Station
Compatibility	Includes TS Wall Mount Reader	Connects with any Wiegand Reader
Dimensions	H: 5.375" x W: 5" x D: 7.5"	H: 4.75" x W: 5" x D: 7.5"
Weight	4.5 lbs (2.04 kg)	4.0 lbs (1.81 kg)
Protocol	USB Virtual COM, ASCII	
Power	14 VDC transformer (included)	
Color/Material	Black, Metal frame	
Warranty	2 year limited	

These devices are for direct enrollment into Velocity. Consider the WaveID® Enrollment Readers for keystroking into Velocity Web Services Client and Primis.